



STANDARD CLAMP

Hard-working hydraulics coupled with a rugged clamp design for handling pallets, bales, drums, boxes, cubed/ unit loads . . . and more.

- **Available in Single Hydraulic Function** — for handling bales, drums or other containers; equal arm movement standard, OR
- **Side-Shifting Double Hydraulic Function** — clamping arms/forks move in unison side-to-side, eliminating need for precise repositioning of lift truck every time the load is lifted and released.
- **Designed for long-life, maximum payload** — lightweight body reduces lost load center, insures years of service.
- **Shoulders of Equal Height** — give better arm support than staggered designs, and offer more uniform distribution of force.
- **Interchangeable, Reversible Components** — aluminum alloy channel bars can be switched out side-to-side, and inverted, to even out wear and extend part life.
- **Pilot-operated Check Valves** — standard feature; prevents loss of clamping pressure.
- **Versatility** — clamp shoulders can be fitted with many optional forks, arms or pads (welded or bolted on) to handle a wide range of needs.
- **Individual Arm Movement** — optional feature; for applications in which one arm is moved alone to enter a stack without repositioning the truck.

Side-Shifting Standard Clamp Dual Hydraulic Function — (Less Arms)

Model No.	Capacity c 24" L.C. (Lbs.)	Opening Range (in.)	Mounting ITA Hook	Weight (Lbs.)	A E T (in.)	C.G. (in.)	Body Width (in.)
SSC30A	3000	18-66	II	385	4.250	2.4	35
SSC31A	3000	8-46	II	365	4.250	2.4	35
SSC40A	4000	18-66	II	500	5.250	2.6	36
SSC50A	5000	20-72	II	625	5.500	3.0	40
SSC50B	5000	20-72	III	635	5.500	3.0	40
SSC51A	5000	20-92	II	850	5.500	3.0	60
SSC51B	5000	20-92	III	850	5.500	3.0	60
SSC65B	6500	17-73	III	1200	6.312	4.5	48
SSC65C	6500	17-73	IV	1200	6.312	4.5	48
SSC100B	9500	17-79	III	1800	6.875	5.0	54
SSC100C	9500	17-79	IV	1800	6.875	5.0	54

Installation of backrest may be required by OSHA or local regulations
(A) Arm shoulders not drilled (B) Consult factory or special opening ranges
(C) Consult factory for special mounting, other than ITA

Standard Clamps Single Hydraulic Function — (Less Arms)

Model No.	Capacity c 24" L.C. (Lbs.)	Opening Range (in.)	Mounting ITA Hook	Weight (Lbs.)	A E T (in.)	C.G. (in.)	Body Width (in.)
SC30A	3000	18-66	II	385	4.250	2.4	35
SC31A	3000	8-46	II	365	4.250	2.4	35
SC40A	4000	18-66	II	500	5.250	2.6	36
SC50A	5000	20-72	II	625	5.500	3.0	40
SC50B	5000	20-72	III	635	5.500	3.0	40
SC51A	5000	20-92	II	850	5.500	3.0	60
SC51B	5000	20-92	III	850	5.500	3.0	60
SC65B	6500	17-73	III	1200	6.312	4.5	48
SC65C	6500	17-73	IV	1200	6.312	4.5	48
SC100B	9500	17-79	III	1800	6.875	5.0	54
SC100C	9500	17-79	IV	1800	6.875	5.0	54

Installation of backrest may be required by OSHA or local regulations



201 W. Oklahoma Ave.
(580) 227-3711

Fairview, OK 73737
FAX 580-227-2165