

ATTACHMENT

DUMP UPENDER

MOUNTS ON ANY FORKLIFT

- **Automatically Handles Many Needs**

able to quickly dump or slowly pour powders, liquids, chemicals, scrap, waste and other material from steel and fiber drums, special hoppers, boxes, trays or wire baskets.

- **Specialized Clamping Pads Available**

standard drum pads (10"W x 18"H) handle both steel and fiber drums; OPTIONAL PADS to handle many other applications: dumping carboys, wire baskets, boxes; upending rolls, bales, and other objects from vertical to horizontal position.

- **Equal Arm Movement, Standard**

assures that the clamping pads grip the load at the same time. Side-shifting is available as an option.

- **Specialized Clamping Pads Available**

standard drum pads (10"W x 18"H) handle both steel and fiber drums; OPTIONAL PADS to handle many other applications: dumping carboys, wire baskets, boxes; upending rolls, bales, and other objects from vertical to horizontal position.

- **180° Forward Tilt**

maximum operator control of dumping process and excellent visibility.



866-283-2759

201 West Oklahoma Ave. - Fairview, OK 73737

580-227-3711 - Fax 580-227-2165

WALDON

www.waldonequipment.com

ATTACHMENT

DUMP UPENDER

THE DUMP UPENDER IS FAST, SAFE AND EFFICIENT

Dumper-Upender*

Dual Hydraulic Function

Model No.	Capacity w/Forks @ 24" L.C. (Lbs.)	Opening Range w/ Dumpers (In.)	Mounting ITA Hook	Fork Length (In.)	Lifting Capacity w/Dumpers (Lbs.)	Body Width (In.)	O.A.C.L. (In.)	C.G. (In.)	Weight (Lbs.)
DUC31A	3000	11-59	II	36	2000	35	32.5	9.0	700
DUC32A	3000	11-59	II	42	1800	35	38.5	12.0	725
DUC33A	3000	11-59	II	48	1500	35	44.5	14.0	750
DUC41A	4000	11-59	II	36	3000	36	33.5	8.6	830
DUC42A	4000	11-59	II	42	2500	36	39.5	11.0	850
DUC43A	4000	11-59	II	48	2000	36	45.5	13.0	870
DUC51A	5000	13-65	II	36	4000	40	34.5	9.6	1250
DUC52A	5000	13-65	II	42	3500	40	40.5	11.3	1270
DUC53A	5000	13-65	II	48	3000	40	46.5	13.5	1290

Side-Shifting Dumper-Upender

Triple Hydraulic Function

SDUC31A	3000	11-59	II	36	2000	35	32.5	9.0	700
SDUC32A	3000	11-59	II	42	1800	35	38.5	12.0	725
SDUC33A	3000	11-59	II	48	1500	35	44.5	14.0	750
SDUC41A	4000	11-59	II	36	3000	36	33.5	8.6	830
SDUC42A	4000	11-59	II	42	2500	36	39.5	11.0	850
SDUC43A	4000	11-59	II	48	2000	36	45.5	13.0	870
SDUC51A	5000	13-65	II	36	4000	40	34.5	9.6	1250
SDUC52A	5000	13-65	II	42	3500	40	40.5	11.3	1270
SDUC53A	5000	13-65	II	48	3000	40	46.5	13.5	1290

866-283-2759

201 West Oklahoma Ave. - Fairview, OK 73737

580-227-3711 - Fax 580-227-2165



www.waldonequipment.com